

A Tutorial for Competent Memetic Algorithms: Model, Taxonomy and Design Issues

Natalio Krasnogor and Jim Smith

Abstract—The combination of Evolutionary algorithms with local search was named “Memetic Algorithms” (MAs) in [1]. These methods are inspired by models of natural systems that combine the evolutionary adaptation of a population with individual learning within the lifetimes of its members. Additionally, MAs are inspired by Richard Dawkin’s concept of a meme, which represents a unit of cultural evolution that can exhibit local refinement [2]. In the case of MAs “memes” refer to the strategies (e.g. local refinement, perturbation or constructive methods, etc) that are employed to improve individuals. In this paper we review some works on the application of MAs to well known combinatorial optimisation problems, and place them in a framework defined by a general syntactic model. This model provides us with a classification scheme based on a computable index D , which facilitates algorithmic comparisons and suggests areas for future research. Also, by having an abstract model for this class of meta-heuristics it is possible to explore their design space and better understand their behaviour from a theoretical standpoint. We illustrate the theoretical and practical relevance of this model and taxonomy for MAs in the context of a discussion of important design issues that must be addressed to produce effective and efficient Memetic Algorithms.

Index Terms—Memetic Algorithms, Evolutionary Global-Local Search Hybrids, Model, Taxonomy, Design Issues.

I. INTRODUCTION

E VOLUTIONARY ALGORITHMS (EAs) are a class of search and optimisation techniques that work on a principle inspired by nature: *Darwinian Evolution*. The concept of natural selection is captured in EAs. Specifically, solutions to a given problem are codified in so-called chromosomes. The evolution of chromosomes due to the action of crossover, mutation and natural selection are simulated through computer code.

It is now well established that *pure* Evolutionary algorithms are not well suited to fine tuning search in complex combinatorial spaces and that hybridisation with other techniques can greatly improve the efficiency of search [3]–[6]. The combination of Evolutionary Algorithms with Local Search (LS) was named “Memetic Algorithms” in [1]. Memetic algorithms (MAs) are extensions of evolutionary algorithms that apply separate processes to refine individuals, for example improving their fitness by hill-climbing.

These methods are inspired by models of adaptation in natural systems that combine the evolutionary adaptation of

a population with individual learning within the lifetimes of its members. The choice of name is inspired by Richard Dawkins’ concept of a meme, which represents a unit of cultural evolution that can exhibit local refinement [2]. In the context of heuristic optimisation a meme is taken to represent a learning or development strategy. Thus a memetic model of adaptation exhibits the plasticity of individuals that a strictly genetic model fails to capture.

In the literature, MAs have also been named Hybrid Genetic Algorithms (e.g. [7]–[9]), Genetic Local Searchers (e.g. [10]), Lamarckian Genetic Algorithms (e.g. [11]), Baldwinian Genetic Algorithms (e.g. [12]), etc. As noted above, they typically combine local search heuristics with the EAs’ operators, but combinations with constructive heuristics or exact methods may also be considered within this class of algorithms. We adopt the name of Memetic Algorithms for this meta-heuristic, because we think it encompasses all the major concepts involved by the other ones, and for better or worse has become the *de facto* standard e.g. [13]–[15].

EAs and MAs have been applied in a number of different areas, for example operational research and optimisation, automatic programming, machine and robot learning. They have also been used to study and optimise models of economies, immune systems, ecologies, population genetics, and social systems, and the interaction between evolution and learning, to name but a few applications.

From an optimisation point of view, MAs have been shown to be both more efficient (i.e. requiring orders of magnitude fewer evaluations to find optima) and more effective (i.e. identifying higher quality solutions) than traditional EAs for some problem domains. As a result, MAs are gaining wide acceptance, in particular in well-known combinatorial optimisation problems where large instances have been solved to optimality and where other meta-heuristics have failed to produce comparable results (see for example [16] for a comparison of MAs against other approaches for the Quadratic Assignment Problem).

II. GOALS, AIMS AND METHODS

Despite the impressive results achieved by some MA practitioners, the process of designing effective and efficient MAs currently remains fairly ad-hoc and is frequently hidden behind problem-specific details. This paper aims to begin the process of placing MA design on a sounder footing. In order to do this we begin by providing some examples of MAs successfully applied to well known combinatorial optimisation problems, and

Manuscript Received December 2003 ;revised September 15 2004 and March 2 2005.

N. Krasnogor is with School of Computer Science and IT, University of Nottingham (email: natalio.krasnogor@nottingham.ac.uk)

J. Smith is with the Faculty of Computing, Engineering and Mathematical Sciences, University of the West of England (email: james.smith@uwe.ac.uk)

draw out those differences which specifically arise from the hybridisation of the underlying EA, as opposed to being design choices within the EA itself. These studies are exemplars, in the sense that they represent a wide range of applications and algorithmic options for a Memetic Algorithm.

The first goal is to define a syntactic model which enables a better understanding of the interplay between the different component parts of an MA. A syntactic model is devoid of the semantic intricacies of each application domain and hence exposes the bare bones of this meta-heuristic to scrutiny. This model should be able to represent the many different parts that compose a MA, determine their roles and interrelations.

With such a model we can construct a taxonomy of MAs, the second goal of this paper. This taxonomy is of practical and theoretical relevance. It will allow for more sensible and fair comparisons of approaches and experimental designs. At the same time it will provide a conceptual framework to deal with more difficult questions about the general behaviour of MAs. Moreover, it will suggest directions of innovation in the design and development of MAs.

Finally, by having a syntactic model and a taxonomy, the process of more clearly identifying which of the many components (and interactions) of these complex algorithms relate to which of these design issues should be facilitated.

The rest of this paper is organised as follows: In Section III we motivate our definition of the class of meta-heuristics under consideration, and give examples of the type of design issues that have motivated this study. This is followed in Section IV by a review of some applications of Memetic Algorithms to well known problems in combinatorial optimisation and bio-informatics. Section V presents a syntax-only model for Memetic Algorithms and a taxonomy of possible architectures for these meta-heuristics is given in Section VI. In Section VII we return to the discussion of design issues, showing how some of these can be aided by the insights given by our model. Finally we conclude with a discussion and conclusions in Section VIII.

III. BACKGROUND

A. Defining the Subject of Study

In order to be able to define a syntactic model and taxonomy we must first clarify what we mean by a Memetic Algorithm. It has been argued that the success of MAs is due to the trade-off between the exploration abilities of the EA, and the exploitation abilities of the local search used. The well known results of MAs over Multi Start Local Search (MSLS) [17] and Greedy Randomised Adaptive Search Procedure (GRASP) [8] suggest that, by transferring information between different runs of the local search (by means of genetic operators) the MA is capable of performing a much more efficient search. In this light, MAs have been frequently described as *Genetic Local Search* which might be thought as the following process [18]:

In each generation of GA, apply the LS operator to all solutions in the offspring population, before applying the selection operator.

Although many MAs indeed use this formula this is a somewhat restrictive view of MAs and we will show in the following sections that many other ways have been used to hybridise EAs with LS with impressive results.

In [19] the authors present an algebraic formalisation of memetic algorithms. In their approach an MA is a very special case of GA where just one period of local search is performed. As we will show in following sections, MAs are used in a *plethora* of alternative ways and not just in the way the formalism introduced in [19] suggests.

It has recently been argued by Moscato that the class of MAs should be extended to contain not only “EA-based MAs”, but effectively include any population-based approach based on a “k-merger” operator to combine information from solutions [13], creating a class of algorithms called the *Polynomial Merger Algorithm (PMA)* (pp227 and 228, *ibid*). However, PMA ignores mutation and selection as important components of the evolutionary meta-heuristic. Rather, it focuses exclusively on recombination, or its more general form, the “k-merger” operator. Therefore we do not use this definition here, as we feel that it is both restrictive (in that it precludes the possibility of EAs which do not use recombination), and also so broad that it encompasses such a wide range of algorithms as to make analysis difficult.

As the limits of “what.is” and “what.is.not” an MA are stretched, it becomes more and more difficult to assess the benefit of each particular component of the meta-heuristic in search or optimisation. *A priori* formalisations such as [13] and [19] inevitably leave out many demonstrably successful MAs and can seriously limit analysis and generalisation of the (already complex) behaviour of MAs. Our intention is to provide an *a posteriori* model of MAs, using *algorithms* as data; that is, applications of memetic algorithms that have been proven successful. It will be designed in such a way to encompass those algorithms. Thus we use a commonly accepted definition, which may be summarised as [20]:

A Memetic Algorithm is an Evolutionary Algorithm that includes one or more local search phases within its evolutionary cycle

While this definition clearly limits the scope of our study it does not curtail the range of algorithms that can fit this scope. As with any formal model and taxonomy, ours will have its own “outsiders”, but hopefully they will be less numerous than those left aside by [13] and [19]. The extension of our model to other population based meta-heuristics is being considered in a separate paper.

Finally we should note that we have restricted the survey part of this paper to Memetic Algorithms approaches for single objective combinatorial optimisation problems (as opposed to multi-objective or numerical optimisation problems). This is not because MAs are unsuited to these domains - they have been very successfully applied to the fields of multi-objective optimisation (see e.g. [21]–[24], an extensive bibliography can be found in [25]), and numerical optimisation (see e.g. [26]–[32]). Rather, the reason for this omission is partly practical, to do with the space this large field would demand. It is also partly because we wish to introduce our ideas in the context of the simple algorithm `StandardLocalSearch(...)` where

it is straightforward to define a neighbourhood, improvement, and the concept of local optimality. When we consider Multi-objective problems, the whole concept of optimality becomes clouded by the trade-offs between objectives, and dominance relations are usually preferred. Similarly in the case of numerical optimisation, the concept of local optimality is clouded by the difficulty, in the absence of derivative information, of knowing when a solution is truly locally optimal, as opposed to say, a point a very small distance away. Nevertheless, it is worth stressing that the issues cloud the exposition, rather than invalidate the concept of “schedulers” which leads to our syntactic model and taxonomy, and the subsequent design guidelines which can equally well be applied in these more complex domains.

B. Design Issues for Memetic Algorithms

Having provided a fairly broad-brush definition of the class of meta-heuristics that we are concerned with, it is still vital to note that the design of “competent” [33] Memetic Algorithms raises a number of important issues which must be addressed by the practitioner.

Perhaps the foremost of these issues may be stated as:

“What is the best trade-off between local search and the global search provided by evolution?”

This leads naturally to questions such as:

- Where, and when, should local search be applied within the evolutionary cycle?
- Which individuals in the population should be improved by local search, and how should they be chosen?
- How much computational effort should be allocated to each local search?
- How can the genetic operators best be integrated with local search in order to achieve a synergistic effect?

As we will see in the following sections, there are a host of possible answers to these questions, and it is important to use both empirical experience and theoretical reasoning in the search for answers. The aim of our syntactic model is to provide a sound basis for understanding and comparing the effects of different schemes. The use of a formal model aids in this by making some of the design choices more explicit, and by providing a means of comparing the existing MA literature with the (far broader) body of research into EAs.

Similarly, while theoretical understanding of the interplay between local and global search is much less developed than that of “pure” EAs, it is possible to look in that literature for tools and concepts that may aid in the design of competent Memetic Algorithms, for example:

- Is a Baldwinian or Lamarckian model of improvement to be preferred?
- What fitness landscape(s) does the population of the Memetic Algorithm operate on?
- What local optima are the Memetic Algorithms operating with?
- How can we engineer Memetic Algorithms that efficiently traverse large neutral plateaus and avoid deep local optima?

IV. SOME EXAMPLE APPLICATIONS OF MEMETIC ALGORITHMS IN OPTIMISATION AND SEARCH

In this section we will briefly comment on the use of MAs on different combinatorial optimisation problems and adaptive landscapes. Applications to *Travelling Salesman Problem (TSP)*, *Quadratic Assignment Problem (QAP)*, *Binary Quadratic Programming (BQP)*, *Minimum Graph Colouring (MGC)*, and *Protein Structure Prediction Problem (PSP)* will be reviewed.

This section does not pretend to be an exhaustive bibliography survey, but rather a gallery of well known applications of MAs from which some architectural and design conclusions might be drawn. In [34] a comprehensive bibliography can be found.

For the definition of the problems the notation in [35] will be used. The reader interested in the complexity and approximability results of those problems is referred to the previous reference. The pseudo-code used to illustrate the different algorithms is shown as used by the respective authors, with only some minor changes made for the sake of clarity.

In [36] a “standard” local search algorithm is defined in terms of a local search problem. Because this standard algorithm is implicit in many MAs, we repeat it here:

```

Standard_Local_Search (x):
Begin
  produce a starting solution s;
  to problem instance x;
  Repeat Until ( locally optimal ) Do
    using s and x generate the next neighbour nx,s;
    If (nx,s is better than s) Then
      s := nx,s;
    Fi
  Od
End.

```

Algorithm `Standard_Local_Search(...)` captures the intuitive notion of searching a neighbourhood as a means of identifying a better solution. It doesn’t specify tie-breaking policies, neighbourhood structure, etc.

This algorithm uses a “greedy” rather than a “steepest” policy i.e. it accepts the first better neighbour that it finds. In general a given solution might have several better neighbours, and the rule that assigns one of the (potentially many) better neighbours to a solution is called a *pivot rule*. The selection of the pivot rule or rules to use in a given instantiation of the standard local search algorithm has tremendous impact on the complexity of the search and potentially in the quality of the solutions explored.

Note also that the algorithm above implies that local search continues until a local optima is found. This may take a long time, and in the continuous domain proof of local optimality may be decidedly non-trivial. Many of the local search procedures embedded within the MAs in the literature are not standard in this sense, that is, they usually perform a shorter “truncated” local search.

A. Memetic Algorithms for the TSP

The *TSP* is one of the most studied combinatorial optimisation problems. It is defined by

Traveling Salesman Problem

Instance: A set C of m cities, and for each pair of cities $c_i, c_j \in C$ a distance $d(c_i, c_j) \in \mathbf{N}$.

Solution: A tour of C , i.e., a permutation $\pi : [1 \dots m] \mapsto [1 \dots m]$.

Measure: The length of the tour, i.e., $d(\pi) = d(\{c_{\pi(m)}, c_{\pi(1)}\}) + \sum_{i=1}^{m-1} d(\{c_{\pi(i)}, c_{\pi(i+1)}\})$.

Aim: minimum length tour $\pi^* : \forall \pi \neq \pi^* \quad d(\pi) > d(\pi^*)$.

In [37] a short review on early MAs for the TSP is presented, where an MA was defined by the following skeleton code:

```

Genetic_Local_Search( $P \in S^l$ ):
Begin
  /*  $\lambda, \mu, m \geq 1$  */
  For  $i := 1$  To  $\mu$  Do
    Iterative_Improvement( $s_i$ );
  Od
  stop_criterion := false;
  While (  $\neg$  stop_criterion ) Do
     $P_I := \emptyset$ ;
    For  $i := 1$  To  $\lambda$  Do
      /* Mate */
       $M_i \in P^m$ ;
      /* Recombine */
       $s_i \in H_m(M_i)$ ;
      Iterative_Improvement( $s_i$ );
       $P_I := P_I \cup \{s_i\}$ ;
    Od
    /* Select */
     $P := (P \cup P_I)^\mu$ ;
    evaluate stop_criterion;
  Od
End.

```

Here we can regard `Iterative_Improvement(...)` as a particular instantiation of `Standard_Local_Search(...)`, and appropriate code should be used to initialise the population, mate solutions and select the next generation. Note that the mutation stage was replaced by the local search procedure. Also a $(\mu + \lambda)$ selection strategy was applied. The use of local search and the absence of mutation is a clear difference between `Genetic_Local_Search(...)` and standard EAs.

In [37] early works on the application of MAs to the *TSP* were commented on. Those works used different instantiations of the above skeleton to produce near optimal solution for small instances of the problem. Although the results were not definitive, they were very encouraging, and many of the following applications of MAs to the *TSP* (and also to other NPO problems) were inspired by those early works.

In [38] the MA `GLS_Based_Memetic_Algorithm(...)` is used which has several non-standard features. For details the reader is referred to [38] and [13]. We are interested here in remarking two important differences with the MA `Genetic_Local_Search(...)` shown previously. In this MA the local search procedure is used after the application of each of the genetic operators and not only once in every iteration of the EA. These two meta-heuristics differ also in that in the last case a clear distinction is made between mutations

and local search. In [38] the local search used is based on the powerful Guided Local Search (GLS) meta-heuristic [39]. This algorithm was compared against MSLS, GLS and a second MA, where the local search engine was the same basic move used by GLS without the guiding strategy. In this paper results were presented from experiments using instances taken from TSPLIB [40] and fractal instances [41]. In no case was the MSLS able to achieve an optimal tour unlike the other three approaches. Out of 31 instances tested the `GLS_Based_Memetic_Algorithm(...)` solved 24 to optimality, MSLS 0, MA with simple local search 10 and GLS 16. It is interesting to note that the paper was not intended as a “better than” paper but rather as a pedagogical paper where the MAs were exposed as a new meta-heuristic in optimisation.

```

GLS_Based_Memetic_Algorithm:
Begin
  Initialise population;
  For  $i := 1$  To  $\text{sizeof}(\text{population})$  Do
     $\text{individual}_i := \text{population}_i$ ;
     $\text{individual}_i := \text{Local} - \text{Search} - \text{Engine}(\text{individual}_i)$ ;
    Evaluate( $\text{individual}_i$ );
  Od
  Repeat Until ( termination_condition ) Do
    For  $j := 1$  To #recombinations Do
      selectToMerge a set  $S_{par} \subseteq \text{population}$ ;
      offspring = Recombine( $S_{par}, x$ );
      offspring = Local - Search - Engine(offspring);
      Evaluate(offspring);
      Add offspring to population;
    Od
    For  $j := 1$  To #mutations Do
      selectToMutate an individual in population;
      Mutate( $\text{individual}$ );
       $\text{individual} = \text{Local} - \text{Search} - \text{Engine}(\text{individual})$ ;
      Evaluate( $\text{individual}$ );
      Add individual to population;
    Od
     $\text{population} = \text{SelectPop}(\text{population})$ ;
    If (population has converged) Then
       $\text{population} = \text{RestartPop}(\text{population})$ ;
    Fi
  Od
End.

```

Merz and Freisleben in [42], [43] and [44] show many different combinations of local search and genetic search for the *TSP* (in both its symmetric *STSP* and asymmetric *ATSP* versions) while defining purpose-specific crossover and mutation operators. In [42] the following code was used to conduct the simulations:

```

STSP-GA:
Begin
  Initialise pop  $P$  with Nearest-Neighbour(...);
  For  $i := 1$  To  $\text{popsize}(P)$  Do
    Lin - Kernighan - Opt( $\text{individual}_i$ ),  $i \in P$ ;
  Od
  Repeat Until ( converged ) Do
    For  $i := 0$  To #crossover Do
      Select two parents  $i_a, i_b \in P$  randomly;
       $i_c = \text{DPX} - \text{STSP}(i_a, i_b)$ ;
      Lin-Kernighan-Opt( $i_c$ );
      With probability  $m_p$  do Mutation-STSP( $i_c$ );
      Replace an individual of  $P$  by  $i_c$ ;
    Od
  Od
End.

```

In this pseudo-code the authors employ specialised crossover and mutation operators for the *TSP* (and a similar algorithm for the *ATSP*). As in previous examples the initial population is a set of local optima, in this case, with respect to `Lin-Kernighan-Opt(...)`. In this case the *LK* heuristic is also applied to the results of crossover and mutation. The authors motivate this, saying

...and let a GA operate on the set of local optima to determine the global optimum

However they also note that this can lead to a disastrous loss of diversity, which prompts their use of a selection strategy which is neither a $(\mu + \lambda)$ nor a (μ, λ) but a hybrid between the two, whereby the new offspring replaces the most similar member of the population, (subject to elitism). As the authors remark, the *Large Step Markov Chains* and *Iterated-Lin-Kernighan* techniques are special cases of their algorithm.

In [44] the authors change their optimisation scheme to one similar to `GLS-Based-Memetic-Algorithm(...)` which has a more traditional mutation and selection scheme and in [43] they use the same scheme as `STSP-GA(...)` but after finalisation of the GA run, post-processing by means of local search is performed.

It is important to notice that Merz and Freisleben's MAs are perhaps the most successful meta-heuristics for *TSP* and *ATSP*, and a predecessor of the schemes described was the winning algorithm of the *First International Contest on Evolutionary Optimisation*.

In [45] Nagata and Kobayashi described a powerful MA with an intelligent crossover, in which the local searcher is embedded in the genetic operator. The authors of [46] describe a detailed study of Nagata and Kobayashi's work, and relate it to the local searcher used by Merz and Freisleben.

B. Memetic Algorithms for the QAP

The *QAP* is found in the core of many practical problems such as facility location, architectural design, VLSI optimisation, etc. Also, the *TSP* and *GP* can be recast as special cases of *QAP*. The problem is formally defined as:

Quadratic Assignment Problem

Instance: A, B matrices of $n \times n$.

Solution: A permutation $\pi : [1 \dots m] \mapsto [1 \dots m]$.

Measure: The cost of the permutation, i.e.,

$$C(\pi) = \sum_{i=1}^{i=n} \sum_{j=1}^{j=n} a_{i,j} \cdot b_{\pi(i),\pi(j)}$$

Aim: Minimum cost permutation $\pi^* : \forall \pi \neq \pi^* C(\pi) > C(\pi^*)$.

Because of the nature of *QAP* it is difficult to treat with exact methods, and many heuristics and meta-heuristics have been used to solve it. In this section we will briefly comment on the application of MAs to the *QAP*.

In [9] the following MA described as a "hybrid genetic algorithm meta-heuristic" is proposed:

```

Genetic_Hybrid_Algorithm( $H_1, H_2$ ):
Begin
   $P := \emptyset$ ;
  For  $i := 1$  To  $m$  Do
    Generate a random permutation  $p$ ;
    Add  $H_1(p)$  to  $P$ ;
  Od
  Sort  $P$ ;
  For  $i := 1$  To number_of_generations Do
    For  $j := 1$  To num_offspring_per_generation Do
      select two parents  $p_1, p_2$  from  $P$ ;
       $child := crossover(p_1, p_2)$ ;
      Add  $H_2(child)$  to  $P$ ;
    Od
    Sort  $P$ ;
    Cull( $P, num\_offspring\_per\_generation$ );
  Od
  Return the best  $p \in P$ ;
End.

```

In the code shown above $H_1(\dots)$ and $H_2(\dots)$ are initialisation and improvement heuristics respectively. In particular the authors reports on experiments where $H_2(\dots)$ is a Tabu Search (TS) heuristic. At the time that paper was written their MA was one of the best heuristics available (in terms of solution quality for standard test instances).

It is interesting to remark that as in `Genetic_Local_Search(...)` and `GLS-Based-Memetic-Algorithm(...)`, the GA is seeded with a high quality initial population, which is the output of an initial local search strategy, H_1 (Tabu Search in this case). Again we find that the selection strategy, represented by `Cull(...)`, is a $(\mu + \lambda)$ strategy as in the previous MAs. The authors further increase the selection pressure by using a mating selection strategy. As in `Genetic_Local_Search(...)`, no explicit mutation strategy is used: Fleurent and Ferland regard $H_1(\dots)$ and $H_2(\dots)$ as mutations that are applied with a probability 1. As in `Genetic_Local_Search(...)`, the optimisation step is applied only to the newly generated individual, that is, the output of the crossover stage.

In [16] results were reported which are improvements to those in the paper previously commented, and for other meta-heuristics for *QAP*. The sketch of the algorithm used is:

```

QAP_MA:
Begin
  Initialise population  $P$ ;
  For  $i := 1$  To  $sizeof(P)$  Do
     $individual := P_i$ ;
     $individual := Local_Search(individual)$ ;
  Od
  Repeat Until ( terminate=True ) Do
    For  $i := 1$  To #recombinations Do
      Select two parents  $i_a, i_b \in P$  randomly;
       $i_c := Recombine(i_a, i_b)$ ;
       $i_c := Local_Search(i_c)$ ;
      Add individual  $i_c$  to  $P$ ;
    Od
     $P := Select(P)$ ;
    If ( Pconverged ) Then
      For  $i := 1$  To  $sizeof(P), i \neq index(Best)$  Do
         $individual := P_i$ ;
         $individual := Local_Search(Mutate(individual))$ ;
      Od
    Fi
  Od
End.

```

Regardless of the new representation and crossover on which the MA relies to perform its search, it should be particularly noted that `Mutation(...)` is applied only when a diversity crisis arises, and immediately after mutating a solution of the population a new local search improvement is performed. Because the selection strategy is again a $(\mu + \lambda)$ strategy, it may be the case that an old individual, i.e. one that survived many generations, goes through local search many times unlike in `GeneticHybridAlgorithm(...)`.

In this case the initial population is obtained by the use of the local search engine. As a marginal comment we can mention that the local search procedure employed was a variant of $2 - Opt(...)$ also known as the *pairwise interchange heuristic*.

C. Memetic Algorithms for the BQP

Binary quadratic programming is defined by:

Binary Quadratic Programming Problem

Instance: Symmetric rational $n \times n$ matrix $Q = (q_{i,j})$.

Solution: Binary vector x of length n .

Measure: The benefit of x , i.e.,

$$f(x) = x^t Q x = \sum_{i=1}^n \sum_{j=1}^n q_{i,j} \cdot x_i \cdot x_j$$

Aim: Maximum benefit solution $x^* : \forall x \neq x^* f(x) < f(x^*)$.

As well as being a well known *NP-Hard* problem, *BQP* has many applications, i.e., financial analysis, CAD problems, machine scheduling, etc. In [47] the authors used an MA with the same architecture as in `QAP_MA(...)` but tailored for *BQP* and they were able to improve over previous approaches based on TS and Simulated Annealing (SA). They also were able to find new best solutions for instances in the ORLIB [48].

D. Memetic Algorithms for the MGC

The *MGC* is one of the most studied problems in graph theory, with many applications in the area of scheduling and timetabling. Its definition is

Graph Coloring

Instance: Graph $G = (V, E)$.

Solution: S , a coloring of G , i.e.,

a partition of V into disjoint sets v_1, \dots, v_k such that each v_i is an independent set for G

Measure: Cardinality k of the coloring

Aim: Minimum k coloring: $S^* : \forall S \neq S^* k(S) \geq k(S^*)$.

In [49] an MA was presented for this problem which used an embedded kind of `StandardLocalSearch(...)` after the mutation stage. The selection strategy used was a generational GA with 1-elitism (the worst individual of the new population is replaced with the best of the previous one) and the algorithm also used some specially designed operators. The authors reported what, at the time the paper was written, were exciting results.

Fleurent and Ferland [50] studied a number of MAs for *MGC* based on the hybridisation of a standard steady state

GA with problem-specific local searchers and Tabu Search. The improvement stage was used instead of the mutation stage of the standard GA. The authors also ran experiments with a problem-specific crossover. The pseudo-code employed in the paper is omitted because of its similarity with `GeneticHybridAlgorithm(...)` already discussed.

In [51] Dorne and Hao' proposed an MA for the *MGC*. This MA used a new crossover, based on the union of independent sets, which is itself a kind of local searcher. The mutation stage was replaced by the powerful Tabu Search. With this MA the authors were able to improve over the best known results of some large instances of the famous *Dimacs benchmarks*. Their algorithm is:

GL_for_Colouring:

```

Begin
  /* f, F*: fitness function and */
  /* best value encountered so far */
  /* s*: best individual encountered so far */
  /* best(P): returns the best individual */
  /* of the population P */
  i=0;
  generate(P0);
  s* := best(P0);
  f* := f(s*);
  While ( f* > 0 and i < maxIter ) Do
    P'i := crossing(Pi, Tx);
    /* using specialised crossover */
    Pi+1 := mutation(P'i);
    /* using Tabu search */
    If ( f(best(Pi+1)) < f* ) Then
      s* := best(Pi+1);
      f* := f(s*);
    Fi
    i := i+1;
  Od
End.

```

E. Memetic Algorithms for the PSP

Protein Structure Prediction is one the most exciting problems that computational biology faces today. In words of John Maynard Smith [52]:

Although we understand how genes specify the sequence of amino acids in a protein, there remains the problem of how the one-dimensional string of amino acids folds up to form a three-dimensional protein... it would be extremely useful to be able to deduce the three-dimensional form of a protein from the base sequence of the genes coding for it; but this is still beyond us.

Because "all-atom" simulations are extremely expensive researchers often resort to a simplified model of the *PSP*. One well studied example is Dill's *HP* model [53]. Despite being a simplification, variations of this model have been shown NP-hard, see for example [54]–[56]. It may be defined as follows:

HP-model of Protein Structure Prediction

Instance: A simplified protein sequence of length l , i.e. a string $s \in \{H, P\}^l$.

Solution: A self-avoiding path p which embeds s into a two or three dimensional lattice (i.e. Z^2 or Z^3)

This defines a *Distance Matrix*, D , of inter-residue distances.

Measure: Potential energy, of the sequence in that fold, approximated by the number of pairs of H-type residues, which are not sequence-adjacent, but are at distance 1 in p

$$E(p) = - \sum_{i=1}^{l-2} \sum_{j=i+2}^l D_{ij} \mid (D_{ij} = 1) \wedge (s_i = s_j = H)$$

Aim: Minimum energy solution $p^* : \forall p \neq p^* E(p) > E(p^*)$.

In [57] we applied the following MA to the *PSP*

```

PF_MA:
Begin
  Random initialise population Parents;
  Repeat Until ( Finalisation.criteria.met ) Do
    Local_Search(Parents);
    mating_pool := Select_mating(Parents);
    ofsprings := Cross(mating_pool);
    Mutate(offsprings);
    Parents := Select(Parents + ofsprings);
  Od
End.

```

This algorithm was able to find optimum configurations for 19 out of 20 protein instances of moderate size, out performing a GA with identical architecture except for the use of `Local_Search(...)`. In this MA a $(\mu + \lambda)$ replacement strategy was used, together with fitness-proportionate selection for mating. In contrast to all the previous MA, in this scheme `Local_Search(...)` is considered a “first class” operator. It receives the entire population and applies with probability p_{ls} a complex local search algorithm to each individual. Under this scheme, solutions are improved during all their life span. In [58] several MAs for other molecular conformation problems are briefly commented on. In [59] a comparison of Simulated Annealing against GA and Local Search hybrids is presented for the closely related *Drug Docking* domain. In [60] a co-evolutionary memetic approach is introduced while in [61] the authors introduce a memetic crossover for the *PSP*.

V. A SYNTACTIC MODEL FOR MEMETIC ALGORITHMS

A. A Syntactic Model for Evolutionary Algorithms

Following [62] the Evolutionary Algorithm can be formalised within a “Generate-and-Test” framework by:

$$GA = (P^0, \delta^0, \lambda, \mu, l, F, G, U)$$

- $P^0 = (a_1^0, \dots, a_\mu^0) \in I^\mu$ Initial population
- $I = \{q_1, \dots, q_n\}^l$ n -ary finite discrete problem representation
- $\delta^0 \subseteq \mathfrak{R}$ Initial parameter set for operators
- $\mu \in \mathbf{N}$ Population size
- $\lambda \in \mathbf{N}$ Number of offspring
- $l \in \mathbf{N}$ Length of representation
- $F : I \mapsto \mathfrak{R}^+$ Fitness function
- $G : I^\mu \mapsto I^\lambda$ Generating Function
- $U : I^\mu \times I^\lambda \mapsto I^\mu$ Updating function

Note that in this model we consider the effects of survivor selection at the end of one generation, and parent selection at

the start of the next, to be amortised into a single function U which is responsible for updating the working memory of our algorithm. The Memetic Algorithms’ literature, as does the general EA literature, contains examples of the incorporation of diversity-preservation measures into U . These have included implicit measures, such as the imposition of spatial structure on the population (e.g., [42], [63], [64]) or explicit measures such as duplicate prevention (e.g. [65], [66]). This issue will be discussed in more depth in Section VII

Examples of G as generating functions are mutation and crossover operators. A recombination operator has as its signature¹ $R : I^\mu \times \delta \mapsto I$ and a mutation operator $M : I \times \delta \mapsto I$. The initial values for parameters of the operators used (e.g. mutation probabilities) are represented by δ^0 . If $O \in I^\lambda$ denotes the set of offspring then an iteration of the GA is:

$$\begin{aligned} O_i^t &= M(R(P^t, \delta^t), \delta^t) \quad \forall i \in \{1, \dots, \lambda\} \\ P^{t+1} &= U(O^t \cup P^t), \end{aligned} \quad (1)$$

where t is the time step.

Although the formalisation above assumes a finite discrete problem representation with each element of the representation having the same arity, this is done simply for the sake of clarity, and the framework permits the use of any desired representation via suitable redefinition of I .

B. Extension to Memetic Algorithms

We will need to extend this notation to include local search operators as new generating functions. We define these to be members of a set, $\mathcal{L} = \{L_1, \dots, L_m\}$, of local search strategies available to the MA.

Examples of so called “Multimeme Algorithms” where the local search phase has access to several distinct local searchers (i.e. $m > 1$) can be found in [20] and [67]. The signature of each member of the set \mathcal{L} is $L_j : I^{c_1} \times \zeta \mapsto I^{c_1}$ where ζ is a strategy-specific parameter (with a role equivalent to δ), j is an index into the set \mathcal{L} and c_1 is a constant that determines how many solutions the local searcher uses as its argument and how many solutions it returns. In general we will assume that $c_1 = 1$, and consequently drop the subscript for the sake of clarity, but as an example of a local searcher with $c_1 = 2$ the reader might consider Jones’ Crossover Hill Climber [68].

As can be seen from the pseudo-code in the previous sections, the local search stage can happen before or after crossover, mutation and selection or in any imaginable combination, and the local searchers are members of a (potentially) large set of alternative heuristics, approximate or exact algorithms with which solutions could be improved.

To model this we define entities called *schedulers* which are higher order functions.² An early example of the application of higher order functions to memetic algorithms see [69], where the authors implement Radcliffe and Surry’s formalism [19] in a functional language.

¹Note that the use of the superscript μ permits the modelling of crossover operators with variable arity, e.g., Moscato’s K -mergers

²A higher order function or functional is a function whose domain is itself a set of functions, e.g., the indefinite integral of a function is a higher order function.

C. Co-ordinating Local Search with Crossover and Mutation

The *fine grain scheduler* (fS) co-ordinates when, where and with which parameters local searchers from \mathcal{L} will be applied during the mutation and crossover stages of the evolutionary cycle. It has the following signature:

$$fS : (I^{c_1} \times \delta \mapsto I) \times \mathcal{L} \times I^{c_1} \times \delta \times \zeta \mapsto I$$

The fS receives three arguments. The first is a generating function with signature $I^{c_1} \times \delta \mapsto I$, that is, recombination (with $c_1 = \mu$) or mutation (with $c_1 = 1$). The second is a set of local searchers to be scheduled, which have signatures $I^{c_2} \times \zeta \mapsto I^{c_2}$. Usually c_2 will have the value 1: for example in most of the examples above local search is applied *after* recombination or mutation. However our model should not rule out other possibilities - for example doing local search on the parents *before* recombination, in which case $c_2 = c_1$. Finally it receives a set of solutions by means of the I^{c_1} and operators and two sets of strategy specific parameters δ and ζ . In the simplest case there will be a mutation (fS_M) and a recombination (fS_R) schedulers with the following signatures:

$$\begin{aligned} fS_M & : (I \times \delta \mapsto I) \times \mathcal{L} \times I \times \delta \times \zeta \mapsto I \\ fS_R & : (I^\mu \times \delta \mapsto I) \times \mathcal{L} \times I^\mu \times \delta \times \zeta \mapsto I \end{aligned}$$

To illustrate this point, consider the case where a single local search method is used: $fS_M(M, L_1, i, \delta, \zeta_1)$ where i is an individual, M is a mutation operator, and L_1 is the local searcher with parameters ζ_1 . Note that we are not specifying how M and L_1 will be used “inside” the scheduler. As examples of how the scheduler might operate consider a simple case where mutation M is applied to i and the result of this operation is given as an argument to L_1 . The symmetric case is equally valid i.e applying mutation M to the result of improving i with L_1 . More complex scenarios can be imagined, it is up to fS to organise the correct pairing of inputs/outputs to functions.

A similar case can be stated for $fS_R(R, L_2, Q, \delta, \zeta_2)$, where in this case we are receiving as actual parameter a population of individuals Q (usually a subset of P) rather than a single individual.

An illustration of this can be found in [46] where the authors argue in favour of encapsulating a $2\text{-OPT}(\dots)$ local searcher into an algorithm with Nagata’s and Kobayashi’s *Edge Assembly Crossover* [45]. The latter is a good example of an “intelligent” crossover operator which uses information about edge lengths to construct an offspring by connecting sub-tours common to both parents. However in both the Nagata and Kobayashi’s original algorithm, and Watson et. al.’s “improved” version the crossover operator is used to generate a single offspring. In the original paper, “Iterative Child Generation” is used, i.e. the scheduler repeatedly applies the crossover operator until a good solution is found, and in Watson’s version, a 2-opt local search is applied **after** the crossover operator.

An even clearer example can be found in [70] where a new crossover for the *Job-shop Scheduling Problem* is proposed. In this case the crossover is a local search procedure that uses a two-solutions based neighbourhood. In other words we

can make a clear distinction between a generating operator that only ever considers one or two potential offspring, (even if it “intelligently” uses heuristics such as edge distances in its construction phase) and one that constructs and evaluates several solutions before returning an offspring. The latter case clearly is that of a scheduled local search, where the “neighbourhood” of a [pair of] point[s] is defined by the action of a generating operator.

D. Co-ordinating Local Search with Population Management

An alternative model, as illustrated in Section IV-E, is to co-ordinate the action of local search with the population management and updating functions. A *Coarse Grain Scheduler* (cS) is defined by:

$$cS : (I^\mu \times I^\lambda \mapsto I^\mu) \times \mathcal{L} \times I^\mu \times I^\lambda \times \delta \times \zeta \mapsto I^\mu$$

In this scheduler the formal parameters stand for the updating function U , the set of the local searchers \mathcal{L} , the sets of parents and offspring (I^μ and I^λ respectively), and the operator specific parameter sets δ and ζ . The goal of this scheduler is to organise the application of a local searcher to either the set of parents, the set of offspring or to their union. The difference between a coarse grain scheduler and a fine grain scheduler is that the former can provide population statistics to its local search operator while the fine grain scheduler knows just one individual at a time (or two for the one associated with crossover).

By the introduction of the local search schedulers we can simulate any of the algorithmic combinations above. Also, by using a **set** of local searchers by the schedulers we can model powerful multi-operator hybrid strategies like those described in [71], [72] and [73]. We can also include the approaches discussed in [74] and [75] where partial Lamarckianism or “sniffs” rather than complete local searches are allowed and allocated dynamically during the search. Further, it is possible to model the local search methods described in [26] where statistics from the population are used to apply local search selectively. Another interesting example of the use of coarse grain schedulers can be seen in [76] where a hybrid meta-heuristic is introduced which uses concepts of both evolutionary algorithms and gradient search. Under this scheme potentially all the individuals in the populations are continuously “learning” since each stage of Local Search may be truncated rather than continue to local optimality.

E. Incorporating Historical Information

The natural extension to this model is to introduce a *meta scheduler* (mS) with the following signature:

$$mS : \mathcal{L} \times H_P^t \times I^\mu \times \delta \times \zeta^t \mapsto I^\mu$$

where $H_P^t \subseteq P_1 \cup P_2 \cup \dots \cup P_{t-1}$.

The meta scheduler is able to use information from previous populations to influence its search by means of ζ and the elements of \mathcal{L} , hence a kind of evolutionary memory is introduced into the evolutionary search mechanisms. Note that in these cases the parameter sets ζ associated with the

schedulers may now represent complex data structures rather than simple probability distributions.

With the introduction of this scheduler, a new class of meta-heuristics is available given by the many possible instantiations of:

$$\begin{aligned} O_i^t &= fS_M(M, \mathcal{L}, fS_R(R, \mathcal{L}, P^t, \delta^t, \zeta^t), \delta^t, \zeta^t) \\ &\quad \forall i \in \{1, \dots, \lambda\} \\ P^{t+1} &= mS(\mathcal{L}, H_P^t, cS(U, \mathcal{L}, P^t, O^t, \delta^t, \zeta^t), \delta^t, \zeta^t) \end{aligned} \quad (2)$$

where the use of superscripts t recognises that the several parameters may be time-dependant. We have not found this kind of MAs in the literature, yet they represent a novel, qualitatively different and perhaps powerful family of MAs. As an example of its use, one can imagine that the elements of \mathcal{L} are based on Tabu search and that the meta scheduler uses the information of ancient populations to update their Tabu lists, thus combining global and local information **across time**. An advantage of considering meta-schedulers which affect ζ , is that by setting all elements of \mathcal{L} to the identity function, it is possible to include within our model the work on Adaptive GAs which use a *history* of previous results to update the probabilities of applying genetic operators, such as those described in [77]–[79]. Furthermore the more recent approach to optimisation called “Hyper-heuristics”, in particular those described in [80], [81] can be considered to be Multimeme algorithms where the set of low level operators (i.e. local searchers and constructive heuristics) are adaptively applied to one solution ($\lambda = \mu = 1$) by the meta-scheduler (called hyper-manager in hyper-heuristics terminology).

VI. A TAXONOMY FOR MEMETIC ALGORITHMS

A. A Scheduler-Based Taxonomy

With the use of Eqn. (2), it is possible to model the vast majority of the MAs found in the literature, capturing the interaction between local search and the standard evolutionary operators (mutation, crossover, selection). From this syntactic model a taxonomy of architectural classes can be naturally derived based on an index number $D(A)$ which can be ascribed to any MA (A).

$D(A) = b_{mS}b_{cS}b_{fS_R}b_{fS_M}$ is a four bit binary number with each b_i taking the value 0 or 1 according to whether scheduler i is absent, respectively present, in A . To understand the ordering of the bits, note that the least significant bit is associated to the scheduler that receives as one of its arguments at most 1 solution, the next bit to the one that receives at most μ solutions, the next two bits are assigned to the schedulers that employ at most $\mu + \lambda$ or $|2^{P_1 \cup \dots \cup P_{t-1}}|$ solutions respectively in their arguments.

To illustrate this point with examples from the review above, the algorithm `GeneticLocalSearch(...)` has an index $D = 2$ because just the fine grain scheduler associated with crossover and meme is present, while `GLSBasedMemeticAlgorithm(...)` has $D = 3$, since the mutation and crossover schedulers are used.

Table I classify the various methods discussed in section III accordingly to their D number, but it will rapidly be seen that only a small fraction of the alternative MAs were employed

and investigated, and that the pattern is inconsistent across different problem types. Of particular interest are the frontiers for $D \geq 4$ and $D \geq 8$. Although throughout this paper we have concentrated mainly on single objective problems, we have included in this table a reference to [21]. In that paper the authors tackle a Multi-Objective problem using a memetic algorithm with what they call a “non-dominated Pareto archive” as an evolutionary memory. This work represents a clear example of an MA that resides above the frontier $D \geq 8$. It is clear from visual inspection of this table that there are plenty of alternative MAs waiting to be investigated for these problems.

B. Relationship to Other Taxonomies

The taxonomy presented here complements the one introduced in [91] by Caegary et al. who provide a comprehensive taxonomic framework for EAs. They define a “Table of Evolutionary Algorithms” (TEA) where the main features of the design space of evolutionary algorithms are placed in the columns of the table. In a related and complementary work, Talbi [92] provides a general classification scheme for meta-heuristics based on two different aspects of a meta-heuristic: its design space and its implementation space. He then develops a hierarchical organisation for each one. Specifically for the design space of hybrid meta-heuristics, he identifies what he called low-level-relay hybrids (LRH), low-level-cooperative hybrids (LCH), high-level-relay hybrids (HRH) and high-level-cooperative hybrids (HCH). Regarding those two works, MAs can be considered to be represented in Caegary et.al. work with a TEA where the column associated to an improving algorithms always receives a value of “yes”, while in Talbi’s taxonomy an MA could be placed within the LCH class.

Our approach categorises the architecture of a subclass of the algorithms both of the previous taxonomies include. In that way a more refined classification is obtained for the subclass of evolutionary algorithms and hybrid meta-heuristic that are memetic algorithms. Of course such a syntactic model and taxonomy is of little interest to the practitioner unless it in some way aids in the conceptualisation and design process. In the following sections we shall move on to show how the model may be used during the design of an algorithm.

C. Distinguishing Types of Local Search Strategies

Making the separation into two sets of objects (candidate solutions in the EA’s population, and local search heuristics), with interactions mediated by a set of schedulers facilitates a closer examination of the potential nature of the elements of \mathcal{L} . In keeping with the name given to this class of algorithms, so coincidentally very much in the spirit of his idea, we will adapt Dawkins’ original definition and call each $L \in \mathcal{L}$ a “meme”. Metaphorically speaking, memes can be thought of as representing alternative improvement strategies that could be applied to solutions, where these strategies may be imitated, improved, modified, etc.

The model presented in Eq. (2) already allows us to distinguish and define three cases:

- If $L^t = L^0 \forall t$ then we call L a *static meme*.

9 - 15							
8							[21]
7						[76]	[82]
6		[16]		[47]			
5							[83]
4	[57]				[57], [59]	[26], [74], [84], [85]	
3	[13], [38], [44]					[86]	[87], [88]
2	[37], [42], [43], [45], [46]	[9]	[50], [51]				
1			[49]				[89], [90]
0							
D	TSP	QAP	MGC	BPQ	PPF and Protein Docking	General Studies	Other Applications

TABLE I

CLASSIFICATION OF ALGORITHMS DISCUSSED IN SECTION III ACCORDING TO PROBLEM AND D .

- If L^t adapts through changes in its parameters ζ^t as t increases then we call L an *adaptive meme*.
- If L^t adapts through changes in L itself, e.g. by evolving under a GP approach, (and possibly in ζ^t also) then we call L a *self-adaptive meme*.

It is important to realise that it is sufficient for any $L \in \mathcal{L}$ to be adaptive to make the whole set of memes into an adaptive meme set. In the same way, if just one L^t is self-adaptive then the entire \mathcal{L} is self-adaptive³.

To the best of the authors' knowledge the only memetic algorithms that scheduled more than one static local searcher at a time are those described in [71]–[73]. Almost all the papers studied in this work use single static memes with the exceptions of the algorithms described in [76] (if the momentum term is included into the model described therein), `GLS_Based_Memetic_Algorithms(...)` and `PF_MA(...)`. As examples of self-adaptive memes we refer the reader to the more recent [93]–[98].

The extension to considering a *set* of adaptive or self-adaptive memes, rather than a single local search method, gives rise to an extra level of complexity in the schedulers. The simplest case uses static memes and requires that ζ is enlarged to include a probability distribution function (pdf) for the likelihood of applying the different memes, in addition to their operational parameters. More complex cases might involve a different pdf for each scheduler.

The simplest adaptive case requires that ζ is time-dependent, with the scheduler becoming responsible for adapting the pdf. In more complex scenarios it might be necessary to store a different pdf for each member of the population - i.e. individual rather than population level adaptation in the terminology of [99], [100]. Allowing for adaptivity within MAs makes it necessary to couple the adaptation over time of ζ and \mathcal{L} to the evolutionary equation (2).

VII. DESIGN ISSUES FOR “COMPETENT” MEMETIC ALGORITHMS

In [33] Goldberg describes “competent” Genetic Algorithms as:

genetic algorithms that solve hard problems quickly, reliably, and accurately.

³For the sake of clarity of the model we have left out the minor signature modifications that are needed to reflect the fact that a meme might change its arguments or change itself.

As we have described above, for a wide variety of problems, Memetic Algorithms *can* fulfil these criteria better than traditional Evolutionary Algorithms. However the simple inclusion of a given local search method is not enough to increase the competence of the underlying EA. Rather, the design of “competent” Memetic Algorithms raises a number of important issues. It is now appropriate to revisit these issues, in the light of our syntactic model and taxonomy, in order to see what new insights can be gained. While we are not suggesting that all implementations of MAs should follow the scheduler-based view-point, we would argue that it is certainly beneficial to consider this perspective to inform design decisions.

To re-cap, some of the principal design issues are:

- What Local Search Operator should be used?
- Which fitness landscape(s) is the MA navigating?
- With what local optima is the MA operating?
- Where, and when, should local search be applied within the evolutionary cycle?
- Is a Baldwinian or Lamarckian model to be preferred?
- How can the genetic operators best be integrated with local search in order to achieve a synergistic effect?
- How can we engineer MAs that can efficiently traverse large neutral plateaus and avoid deep local optima?
- Which individuals in the population are to be improved by local search and how do we choose among them?
- How much cpu budget will be allocated to the local search?

We now discuss these items according to the grouping above.

A. Choice of Local Search Operators

The reader will probably not be surprised to find that our answer to the first question is “*it depends*”. In [67] we showed that even within a single problem class (in that case TSP) the choice of which single LS operator gave the best results when incorporated in an MA was entirely instance-specific. Furthermore, studies of the dynamic behaviour of various algorithms (including Multi-Meme MAs) showed that in fact the choice of which LS operator yielded the biggest improvements was also time-dependent.

It is well known that most meta-heuristics suffer from getting trapped in local optima. It is also trivially true that a point which is locally optimal with respect to one operator may not be with respect to another (unless it is globally optimal). Taking these points together has motivated recent work into meta-heuristics such as *Variable Neighbourhood Search* [101], which utilise multiple local search operators.

In earlier sections we have listed a number of papers in the recent MA literature which use multiple LS operators, and we would certainly argue that faced with a choice of operators, a sensible design approach would be not to decide *a priori* but to incorporate several. Given such an approach, for the sake of efficiency it is worth considering methods to avoid spending time utilising non-productive operators, which implies at least some way of adapting the operator probabilities in ζ . This in turn implies a coarse-grain or meta scheduler is present. It is perhaps worth noting that in [95] it was shown that while coarse-grain adaptation of ζ was sufficient for a *steepest – ascent* LS, the extra noise inherent in an *first – ascent* approach gave worse results. It was suggested that in such a case using a “history” of relative performance gains, as per Paredis’ LTFE would be beneficial - in other words a meta-scheduler.

Related to this point are the two more theoretical issues concerning landscape and local optima. Merz et.al in [10], [102], [103] employ the concept of fitness landscape distance correlation to assess the behaviour of MAs. Although the correlation measures discussed in those papers can provide very valuable indications on the likely performance of MAs, they can sometimes be misleading. In particular, as a fitness distance correlation is measured based on one particular move operator (e.g. local searcher), if any of the schedulers in Eqn. (2) has access to more than one local searcher then different fitness landscapes will need to be considered. This fact was recognised by Jones’ “One Operator, One Landscape” axiom [104].

B. Integration into EA cycle

We have grouped together the next three issues in our list as they are intimately related, and there has been some confusion in the previous literature.

Some researchers [18] consider that when the LS operator is applied *before* crossover and mutation then the MA is a “Lamarckian” algorithm, and when the LS operator is applied *after* crossover and mutation it is a pure “Darwinian” algorithm. This is an erroneous interpretation of Lamarckian vs. Baldwin Learning. In both cases local search is used to improve (if possible) the fitness of the candidate solution, thus changing its selection probabilities. The difference is simply that in the case of Lamarckian (but not Baldwinian) learning the modifications are also assimilated into the individual – in other words the fitter neighbour *replaces* the original candidate solution. As is clearly illustrated in the case of `GLS_Based_Memetic_Algorithm(...)`, Lamarckian learning in MAs can happen before or after the application of the other genetic operators. However there is little point in applying Baldwinian search after parent selection but before recombi-

nation and mutation, since the resultant offspring will need to be re-evaluated anyway.

If a Lamarckian local search is continued to optimality, then on average the recombination and mutation are likely to reduce the fitness of a solutions which were previously locally optimal. The hoped-for synergy in such an MA is that the use of genetic variation operators will produce offspring which are more likely to be in the basin of attraction of a high-quality local optimum than simply randomly selecting another point to optimise. Clearly in order to achieve this synergy, i.e. to avoid selection discarding these new points, it is a good idea to perform local search on these offspring prior to selection. In other words an algorithm “Select–local search – probabilistically recombine – probabilistically mutate –select ...” makes little sense.

In practice, most recent work has tended to use a Lamarckian approach, and the papers cited by Merz and Freisleben are typical in their (highly successful) advocacy of running the local search to optimality. However as noted in Section IV, simply incorporating one or more powerful local searchers into an EA can lead to a rapid loss of diversity if steps are not taken to prevent this during the design phase. This has clear implication for the likelihood of the algorithm getting stuck in local optimum, or “stagnating” on a plateau.

The use of coarse-grain schedulers provides a simple means of avoiding this by monitoring population convergence statistics. In `QAP_MA(...)` this is done by monitoring convergence then applying vigorous mutation to the whole population. An alternative approach can be seen in [20], [57] which utilises a Boltzmann criteria in the pivot rule of local search, with the inverse of the population fitness range determining the temperature, and hence the likelihood of accepting a worse neighbour in a local search.

C. Managing the Global-Local Search Trade-off

The majority of MAs in the literature apply local search to every individual in every generation of the evolutionary algorithm, our model makes it clear that this is not mandatory. In [26] and [74] the authors explore these issues and suggest various mechanisms by which individuals are chosen to be optimised by local search, the intensity of local search and the probability of performing the local optimisation. They achieve this by providing sophisticated coarse grain schedulers that measure population statistics and take them into consideration at the time of applying local search.

In [74] Land addresses the problem of how to best integrate the local search operators with the genetic operators. He proposes the use of fine grain schedulers, both for mutation and crossover, that “sniff” (sample) the basin of attraction represented by a solution. That is, instead of performing a complete local search in every solution generated by the evolutionary operators, a partial local search is applied; only those solutions that are in promising basin of attraction will be assigned later (by the coarse grain scheduler) an extended cpu budget for local search. In a similar spirit Krasnogor in [20] proposes “crossover-aware” and “mutation-aware” local searchers.

In [71] and [57] the issue of large neutral plateaus and deep local optima is addressed by providing modified local searchers that can change their behaviour accordingly to the convergence state of the evolutionary search. As we have noted above, a different approach to avoid getting trapped in a local optimum is to use various local searchers simultaneously in the population. In [67], [72] and [73] the authors resort to that technique to improve the robustness of the Memetic Algorithms.

VIII. CONCLUSIONS AND FURTHER WORK

In this work we committed ourselves to the study of several works on Memetic Algorithms, coming from different sources, with the purpose of designing a syntactical model for MAs. In contrast with [19] where an *a priori* formal memetic algorithm is given, ours is an *a posteriori* formalisation based on the papers cited here and several others.

The syntactical model obtained allowed for the definition of an index number D into the taxonomy of MAs implicit in Eq. 2. When plotting the D index for a number of papers we were able to identify classes of MAs that had received a lot of attention and other classes that were little explored from a theoretical and practical point of view. For example, we found no representatives of MAs (for mono objective optimisation) with $D > 7$, although their counterparts are well known in the GA literature and in the multi-objective MA literature.

Furthermore, our syntactical model suggests the existence of a novel class of meta-heuristic in which four schedulers interact. The reader should note that while a higher D value implies a more complex algorithm it does not necessarily result in a better algorithm; all things being equal, a lower D algorithm should be preferred to one with a larger D .

We were able to identify two kinds of helpers, static and adaptive, and to generalise a third type: self-adaptive helpers. Whilst examples were found of the first two types, the third type was just recently explored [93]–[98] suggesting another interesting line of research.

The adaptation of the index D to reflect the kind of helpers being used by the schedulers is straightforward.

Another important avenue of research is the study of which kind of MA, defined by its D index, is suitable for different types of problems. As shown in the second graph, just a few MAs' architectures were studied for each of the problem surveyed, it remains to be seen whether there are structural or merely historical reasons for the grouping observed. Our taxonomy complements the taxonomies in [91] and [92]. Both the syntactic model and the taxonomy aids our understanding of the design issues involved in the engineering of Memetic Algorithms.

Finally we were able to revisit a list of important design questions and reconsider them in the light of our model, which offered us some new insights and ways of seeing common threads in disparate successful MAs. While we are not suggesting that all implementations of MAs should follow this scheduler-based viewpoint, we would argue that it is certainly beneficial to consider this perspective to inform design decisions.

a) *Acknowledgements:* Natalio Krasnogor wants to acknowledge insightful discussions with Samad Ahmadi, Steve Gustafson, David Pelta and William Hart. The authors would like to thank the anonymous reviewers for their valuable comments.

REFERENCES

- [1] P. Moscato, "On evolution, search, optimization, genetic algorithms and martial arts: Towards memetic algorithms," California Institute of Technology, Pasadena, California, USA, Tech. Rep. Caltech Concurrent Computation Program, Report. 826, 1989.
- [2] R. Dawkins, *The Selfish Gene*. Oxford University Press, New York, 1976.
- [3] L. Davis, *Handbook of Genetic Algorithms*. Van Nostrand Reinhold, New York, 1991.
- [4] D. Wolpert and W. Macready, "No free lunch theorems for optimization," *IEEE Transactions in Evolutionary Computation*, vol. 1, no. 1, pp. 67–82, 1997.
- [5] J. Culberson, "On the futility of blind search: An algorithmic view of "no free lunch"," *Evolutionary Computation*, vol. 6, no. 2, pp. 109–128, 198.
- [6] D. Goldberg and S. Voessner, "Optimizing global-local search hybrids," in *GECCO-99: Proceedings of the Genetic and Evolutionary Computation Conference*, W. Banzhaf, J. Daida, A. Eiben, M. Garzon, V. Honavar, M. Jakaiela, and R. Smith, Eds. Morgan Kaufmann, 1999, pp. 220–228.
- [7] L. He and N. Mort, "Hybrid genetic algorithms for telecommunications network back-up routeing," *BT Technology Journal*, vol. 18, no. 4, pp. 42–56, 2000.
- [8] M. Vazquez and L. Whitley, "A hybrid genetic algorithm for the quadratic assignment problem," in *GECCO-2000: Proceedings of the Genetic and Evolutionary Computation Conference*, D. Whitley, D. Goldberg, E. Cantu-Paz, L. Spector, I. Parmee, and H.-G. Beyer, Eds. Morgan Kaufmann, 2000, pp. 135–142.
- [9] C. Fleurent and J. Ferland, "Genetic Hybrids for the Quadratic Assignment Problem," in *DIMACS Series in Discrete Mathematics and Theoretical Computer Science*. American Mathematical Society, 1993.
- [10] P. Merz, *Memetic Algorithms for Combinatorial Optimization Problems: Fitness Landscapes and Effective Search Strategies*. Ph.D. Thesis, Parallel Systems Research Group. Department of Electrical Engineering and Computer Science. University of Siegen., 2000.
- [11] G. M. Morris, D. S. Goodsell, R. S. Halliday, R. Huey, W. E. Hart, R. K. Belew, and A. J. Olson, "Automated docking using a lamarkian genetic algorithm and an empirical binding free energy function." *J Comp Chem*, vol. 14, pp. 1639–1662, 1998.
- [12] K. Ku and M. Mak, "Empirical analysis of the factors that affect the Baldwin Effect," *PPSN-V: Parallel Problem Solving From Nature, Proceedings 1998. Lecture Notes in Computer Science*, pp. 481–490, 1998.
- [13] P. Moscato, "Memetic algorithms: A short introduction," in *New Ideas in Optimization*, D. Corne, F. Glover, and M. Dorigo, Eds. McGraw-Hill, 1999, pp. 219–234.
- [14] W. Hart, N. Krasnogor, and J. Smith, Eds., *Recent Advances in Memetic Algorithms*. Springer, 2004.
- [15] J. Smith, W. Hart, and N. Krasnogor, "Special Issue on Memetic Algorithms," *Evolutionary Computation*, vol. 12, no. 3, pp. 273–353, 2004.
- [16] P. Merz and B. Freisleben, "A comparison of memetic algorithms, tabu search, and ant colonies for the quadratic assignment problem," in *Proceedings of the 1999 International Congress of Evolutionary Computation (CEC'99)*, Washington DC, USA, 1999, pp. 2063–2070.
- [17] E. Marchiori, "Genetic, iterated and multistart local search for the maximum clique problem," in *Applications of Evolutionary Computing, LNCS 2279*. Springer, 2002, pp. 112–121.
- [18] T. Ibaraki, "Combination with local search," in *Handbook of Genetic Algorithms*, T. Back, D. Fogel, and Z. Michalewicz, Eds. Intitute of Physics Publishing and Oxford University Press, 1997, pp. D3.2:1–D3.2:5.
- [19] N. Radcliffe and P. Surry, "Formal Memetic Algorithms," in *Evolutionary Computing: AISB Workshop*, ser. Lecture Notes in Computer Science, T. Fogarty, Ed., vol. 865. Springer-Verlag, Berlin, 1994, pp. 1–16.

- [20] N. Krasnogor, "Studies on the theory and design space of memetic algorithms," Ph.D. dissertation, University of the West of England, Bristol, United Kingdom., 2002, <http://www.cs.nott.ac.uk/~njk/papers.html>.
- [21] J. Knowles and D. Corne, "M-paes: A memetic algorithm for multi-objective optimization," *Proceedings of the Congress on Evolutionary Computation (CEC2000)*, vol. 1, pp. 325–332, 2000.
- [22] —, "A comparison of diverse approaches to memetic multiobjective combinatorial optimization," in *First Workshop on Memetic Algorithms, Workshop Program Proceedings of the 2000 Genetic and Evolutionary Computation Conference*, A. Wu, Ed. Morgan Kaufmann, 2000, pp. 103–108.
- [23] —, "A comparative assessment of memetic, evolutionary, and constructive algorithms for the multiobjective d-mst problem," in *Second Workshop on Memetic Algorithms, Workshop Program Proceedings of the 2001 Genetic and Evolutionary Computation Conference*, R. Heckendorn, Ed. Morgan Kaufmann, 2001, pp. 162–167.
- [24] E. Talbi, M. Rahoud, M. Mabed, and C. Dhaenens, "New genetic approach for multicriteria optimization problems," in *First International Conference on Evolutionary Multi-Criterion Optimization - EMO 01, Lecture Notes in Computer Science LNCS No. 1993*, E. Zitzler, K. Deb, L. Thiele, C. Coello, and D. Corne, Eds. Springer Verlag, 2001, pp. 416–428.
- [25] C. C. Coello, "List of references on evolutionary multi-objective optimization," <http://www.lania.mx/~ccoello/EMOO/EMOObib.html>.
- [26] W. E. Hart, "Adaptive global optimization with local search," Ph.D. Thesis, University of California, San Diego, 1994.
- [27] K.-H. Liang, X. Yao, and C. Newton, "Evolutionary search of approximated n-dimensional landscapes," *International Journal of Knowledge-Based Intelligent Engineering Systems*, vol. 4, no. 3, pp. 172–183, 2000.
- [28] K. Liang, X. Yao, and C. Newton, "Lamarckian evolution in global optimisation," in *Proc. of the 26th IEEE International Conference on Industrial Electronics, Control and Instrumentation (IECON2000) and the 3rd Asia-Pacific Conference on Simulated Evolution and Learning*. IEEE Press, Piscataway, NJ, 2000, pp. 2975–2980.
- [29] Y. S. Son and R. Baldick, "Hybrid coevolutionary programming for nash equilibrium search in games with local optima," *IEEE Transactions on Evolutionary Computation*, vol. 8, no. 4, pp. 305–315, 2004.
- [30] Y. S. Ong and A. Keane, "Meta-lamarckian learning in memetic algorithms," *IEEE Transactions on Evolutionary Computation*, vol. 8, no. 2, pp. 99–110, 2004.
- [31] T. Ray and K. Liew, "Society and civilization: An optimization algorithm based on the simulation of social behavior," *IEEE Transactions on Evolutionary Computation*, vol. 7, no. 4, pp. 386–396, 2003.
- [32] M. Lozano, F. Herrera, N. Krasnogor, and D. Molina, "Real-coded memetic algorithms with crossover hill-climbing," *Evolutionary Computation*, vol. 12, no. 3, pp. 273–302, 2004.
- [33] D. Goldberg, *The Design of Innovation: Lessons from and for Competitive Genetic Algorithms*. Kluwer Academic Publishers, 2002.
- [34] P. Moscato, "Memetic algorithms" home page," http://www.densis.fee.unicamp.br/~moscato/memetic_home.html.
- [35] P. Crescenzi and V. Kann, "A compendium of NP optimization problems," <http://www.nada.kth.se/~viggo/problemlist/compendium.html>, 2005, annex to *Complexity and Approximation. Combinatorial Optimization Problems and their Approximability Properties*, Springer 1999.
- [36] D. Johnson, C. Papadimitriou, and M. Yannakakis, "How easy is local search," *Journal of Computer And System Sciences*, vol. 37, pp. 79–100, 1988.
- [37] E. Aarts and G. Verhoeven, "Chapter g9.5: Genetic local search for the traveling salesman problem," in *Handbook of Evolutionary Computation*, T. Back, D. Fogel, and Z. Michalewicz, Eds. IOP publishing Ltd and Oxford University Press, 1997, pp. G9.5:1–7.
- [38] D. Holstein and P. Moscato, "Memetic algorithms using guided local search: A case study," in *New Ideas in Optimization*, D. Corne, F. Glover, and M. Dorigo, Eds. McGraw-Hill, 1999, pp. 235–244.
- [39] C. Voudouris and E. Tsang, "Guided local search," *European Journal of Operational Research*, vol. 113, no. 2, pp. 469–499, 1999.
- [40] G. Reinelt, "Tsplib (<http://www.iwr.uni-heidelberg.de/iwr/comopt/soft/tsplib95/tsplib.html>)," mirror site: [gopher://softlib.rice.edu/11/softlib/tsplib](http://softlib.rice.edu/11/softlib/tsplib).
- [41] A. Mariano, P. Moscato, and M. Norman, "Arbitrarily large planar etsp instances with known optimal tours," *Pesquisa Operacional*, vol. 15, pp. 89–96, 1995.
- [42] B. Freisleben and P. Merz, "A Genetic Local Search Algorithm for Solving Symmetric and Asymmetric Traveling Salesman Problems," in *Proceedings of the 1996 IEEE International Conference on Evolutionary Computation*. IEEE Press, 1996, pp. 616–621.
- [43] —, "New Genetic Local Search Operators for the Traveling Salesman Problem," in *Proceedings of the 4th Conference on Parallel Problem Solving from Nature - PPSN IV*, ser. Lecture Notes in Computer Science, H.-M. Voigt, W. Ebeling, I. Rechenberg, and H.-P. Schwefel, Eds., vol. 1141. Springer, 1996, pp. 890–900.
- [44] P. Merz and B. Freisleben, "Genetic Local Search for the TSP: New Results," in *Proceedings of the 1997 IEEE International Conference on Evolutionary Computation*. IEEE Press, 1997, pp. 159–164.
- [45] Y. Nagata and S. Kobayashi, "Edge assembly crossover: A high-power genetic algorithm for the traveling salesman problem," in *Proceedings of the 7th International Conference on GAs*, T. Back, Ed. Morgan Kaufmann, 1997, pp. 450–457.
- [46] J. Watson, C. Ross, V. Eisele, J. Denton, J. Bins, C. Guerra, D. Witley, and A. Howe, "The traveling salesrep problem, edge assembly crossover, and 2-opt," in *Proceedings of PPSN-V: Parallel Problem Solving From Nature*, ser. Lecture Notes in Computer Science. Springer-Verlag, 1998, pp. 823–832.
- [47] P. Merz and B. Freisleben, "Genetic algorithms for binary quadratic programming," in *Proceedings of the 1999 International Genetic and Evolutionary Computation Conference (GECCO'99), Orlando, USA*, 1999, pp. 417–424.
- [48] J. Beasley, "Or-library," in <http://graph.ms.ic.ac.uk/info.html>, 1990, last update November 1999.
- [49] D. Costa, A. Hertz, and O. Dubouis, "Embedding of a sequential procedure within an evolutionary algorithm for coloring problems in graphs," *Journal of Heuristics*, vol. 1, pp. 105–128, 1995.
- [50] C. Fleurent and J. Ferland, "Genetic and hybrid algorithms for graph coloring," *Annals of Operations Research*, vol. 63, pp. 437–461, 1997.
- [51] R. Dorne and J. Hao, "A new genetic local search algorithm for graph coloring," in *Parallel Problem Solving From Nature V*, vol. 1498, Amsterdam, Holland, 1998, pp. 745–754.
- [52] J. M. Smith, *Shaping Life: Genes, Embryos and Evolution*. Weidenfeld and Nicolson, 1998.
- [53] K. A. Dill, "Theory for the folding and stability of globular proteins," *Biochemistry*, vol. 24, pp. 1501–1509, 1985.
- [54] J. Atkins and W. E. Hart, "On the intractability of protein folding with a finite alphabet," *Algorithmica*, vol. 25, no. 2–3, pp. 279–294, 1999.
- [55] B. Berger and T. Leight, "Protein folding in the hydrophobic-hydrophilic (HP) model is NP-complete," in *Proceedings of The Second Annual International Conference on Computational Molecular Biology, RECOMB 98*. ACM Press, 1998, pp. 30–39.
- [56] P. Crescenzi, D. Goldman, C. Papadimitriou, A. Piccolboni, and M. Yannakakis, "On the complexity of protein folding," in *Proceedings of The Second Annual International Conference on Computational Molecular Biology, RECOMB 98*. ACM Press, 1998, pp. 51–62.
- [57] N. Krasnogor and J. Smith, "A memetic algorithm with self-adaptive local search: TSP as a case study," in *GECCO 2000: Proceedings of the 2000 Genetic and Evolutionary Computation Conference*, D. Whitley, D. Goldberg, E. Cantu-Paz, L. Spector, I. Parmee, and H.-G. Beyer, Eds. Morgan Kaufmann, 2000, pp. 987–994.
- [58] P. Moscato, "Memetic algorithms for molecular conformation and other optimization problems," *Newsletter of the Commission for Powder Diffraction, of the International Union of Crystallography*, no. 20, 1998.
- [59] C. D. Rosin, S. Halliday, W. E. Hart, and R. K. Belew, "A comparison of global and local search methods in drug docking," in *Proc 7th Intl Conf on Genetic Algorithms (ICGA97)*, T. Baeck, Ed. San Francisco, CA: Morgan Kaufmann, 1997, pp. 221–228.
- [60] N. Krasnogor, "Co-evolution of genes and memes in memetic algorithms," in *Proceedings of the 1999 Genetic And Evolutionary Computation Conference Workshop Program*, A. Wu, Ed., 1999, p. 371.
- [61] N. Krasnogor, P. M. López, E. de la Canal, and D. Pelta, "Simple models of protein folding and a memetic crossover," in *Exposed at INFORMS CSTS, Computer Science and Operations Research: Recent Advances in the Interface meeting*, 1998.
- [62] J. Smith, *Self Adaptation in Evolutionary Algorithms*. Ph.D. thesis, University of the West of England, 1998.
- [63] M. Gorges-Schleuter, "ASPARAGOS: An asynchronous parallel genetic optimization strategy," in *Proceedings of the Third International Conference on Genetic Algorithms*, J. D. Schaffer, Ed. Morgan Kaufmann Publishers, 1989, pp. 422–427.
- [64] P. Moscato and F. Tinetti, "Blending heuristics with a population-based approach: A memetic algorithm for the traveling salesman problem," Universidad Nacional de La Plata, C.C. 75, 1900 La Plata, Argentina, Report 92-12, 1992.

- [65] S. Ronald, "Preventing diversity loss in a routing genetic algorithm with hash tagging," *Complexity International*, vol. 2, 1995, available at http://journal-ci.csse.monash.edu.au/ci/vol02/sr_hash/.
- [66] C. Fernandez, R. Tavares, C. Munteanu, and A. Rosa, "Using assortative mating in genetic algorithms for vector quantization problems," in *Proceedings of the 2001 ACM symposium on Applied Computing*, ACM press, 2001, pp. 361–365.
- [67] N. Krasnogor and J. Smith, "Emergence of profitable search strategies based on a simple inheritance mechanism," in *GECCO 2001: Proceedings of the 2001 Genetic and Evolutionary Computation Conference*, L. Spector, E. Goodman, A. Wu, W. Langdon, H. Voigt, M. Gen, S. Sen, M. Dorigo, S. Pezeshj, M. Garzon, and E. Burke, Eds. Morgan Kaufmann, 2001, pp. 432–439.
- [68] T. Jones, "Crossover, macromutation, and population based search," in *Proceedings of the Sixth International Conference on Genetic Algorithms*, M. Kauffman, Ed., 1995, pp. 73–80.
- [69] N. Krasnogor, P. Mocchiola, D. Pelta, G. Ruiz, and W. Russo, "A runnable functional memetic algorithm framework," in *Proceedings of the Argentinian Congress on Computer Sciences*. Universidad Nacional del Comahue, 1998, pp. 525–536.
- [70] J. Sakuma and S. Kobayashi, "Extrapolation-directed crossover for job-shop scheduling problems: Complementary combination with JOX," in *GECCO-2000: Proceedings of the Genetic and Evolutionary Computation Conference*, D. Whitley, D. Goldberg, E. Cantu-Paz, L. Spector, I. Parmee, and H.-G. Beyer, Eds. Morgan Kaufmann, 2000, pp. 973–980.
- [71] N. Krasnogor and D. Pelta, "Fuzzy memes in multimeme algorithms: a fuzzy-evolutionary hybrid," in *Fuzzy Sets based Heuristics for Optimization*, J. Verdegay, Ed. Springer, 2002, pp. 49–66.
- [72] R. Carr, W. Hart, N. Krasnogor, E. Burke, J. Hirst, and J. Smith, "Alignment of protein structures with a memetic evolutionary algorithm," in *GECCO-2002: Proceedings of the Genetic and Evolutionary Computation Conference*, W. Langdon, E. Cantu-Paz, K. Mathias, R. Roy, D. Davis, R. Poli, K. Balakrishnan, V. Honavar, G. Rudolph, J. Wegener, L. Bull, M. Potter, A. Schultz, J. Miller, E. Burke, and N. Jonoska, Eds. Morgan Kaufmann, 2002, pp. 1027–1034.
- [73] N. Krasnogor, B. Blackburne, E. Burke, and J. Hirst, "Multimeme algorithms for protein structure prediction," in *Proceedings of the Parallel Problem Solving from Nature VII. Lecture notes in computer science*, 2002, pp. 769–778.
- [74] M. Land, "Evolutionary algorithms with local search for combinatorial optimization," *Ph.D. Thesis, University of California, San Diego*, 1998.
- [75] C. Houck, J. Joines, M. Kay, and J. Wilson, "Empirical investigation of the benefits of partial Lamarckianism," *Evolutionary Computation* 5(1): 31–60., 1997.
- [76] R. Salomon, "Evolutionary algorithms and gradient search: Similarities and differences," *IEEE Transactions On Evolutionary Computation*, vol. 2, no. 2, pp. 45–55, July 1998.
- [77] L. Davis, "Adapting operator probabilities in genetic algorithms," in *Proceedings of the Third International Conference on Genetic Algorithms*, J. Grefenstette, Ed. Morgan Kaufmann, 1989, pp. 61–69.
- [78] D. Corne, P. Ross, and H. Fang, "Fast practical evolutionary timetabling," in *Proceedings of the AISB Workshop on Evolutionary Computation*, T. Fogarty, Ed. Springer Verlag, 1994, pp. 251–263.
- [79] B. Julstrom, "What have you done for me lately?" in *Proceedings of the Sixth International Conference on Genetic Algorithms*, J. Grefenstette, Ed. Morgan Kaufmann, 1995, pp. 81–87.
- [80] P. Cowling, G. Kendall, and E. Soubeiga., "A hyperheuristic approach to scheduling a sales summit," in *Theory of Automated Timetabling PATAT 2000, Springer Lecture Notes in Computer Science*, E. Burke and W. E. editors, Eds. Springer, 2001, pp. 176–190.
- [81] —, "Hyperheuristics: a tool for rapid prototyping in scheduling and optimisation," in *Proceedings of the 2nd European Conference on Evolutionary Computation, EvoCOP 2002. Lecture notes in computer science*. Springer, 2002, pp. 1–10.
- [82] F. Vavak, T. Fogarty, and K. Jukes, "A genetic algorithm with variable range of local search for tracking changing environments," in *Parallel Problem Solving From Nature - PPSN IV*, ser. Lectures Notes in Computer Science - Vol 1141, H. Voigt, I. Rechenberg, and H. Schwefel, Eds. Springer-Verlag, 1996, pp. 376–385.
- [83] G. Dozier, J. Bowen, and A. Homaifar, "Solving constraint satisfaction problems using hybrid evolutionary search," *IEEE Transactions On Evolutionary Computation*, vol. 2, no. 1, pp. 23–33, April 1998.
- [84] S. Tsutsui and A. Ghosh, "Genetic algorithms with a robust solution searching scheme," *IEEE Transactions On Evolutionary Computation*, vol. 1, no. 3, pp. 201–208, September 1997.
- [85] T. Murata, H. Ishibuchi, and M. Gen, "Specification of local search directions in genetic local search algorithms for multi-objective optimization problems," in *Proceedings of the Genetic and Evolutionary Computation Conference (GECCO-99)*, W. Banzhaf, J. Daida, A. Eiben, M. Garzon, V. Honavar, M. Jakiela, and R. Smith, Eds. Morgan Kaufmann, 1999, pp. 441–448.
- [86] P. Merz and B. Freisleben, "On the Effectiveness of Evolutionary Search in High-Dimensional NK-Landscapes," in *Proceedings of the 1998 IEEE International Conference on Evolutionary Computation*. IEEE Press, 1998, pp. 741–745.
- [87] B. Dengiz, F. Altıparmak, and A. Smith, "Local search genetic algorithm for optimal design of reliable network," *IEEE Transactions On Evolutionary Computation*, vol. 1, no. 3, pp. 179–188, September 1997.
- [88] J. Berger, M. Sassi, and M. Salois, "A hybrid genetic algorithm for the vehicle routing problem with time windows and itinerary constraints," in *Proceedings of the Genetic and Evolutionary Computation Conference (GECCO-99)*, W. Banzhaf, J. Daida, A. Eiben, M. Garzon, V. Honavar, M. Jakiela, and R. Smith, Eds. Morgan Kaufmann, 1999, pp. 44–51.
- [89] E. Burke and J. Newall, "A multistage evolutionary algorithm for the timetable problem," *IEEE Transactions On Evolutionary Computation*, vol. 3, no. 1, pp. 63–74, April 1999.
- [90] E. Marchiori and C. Rossi, "A flipping genetic algorithm for hard 3-sat problems," in *Proceedings of the Genetic and Evolutionary Computation Conference (GECCO-99)*, W. Banzhaf, J. Daida, A. Eiben, M. Garzon, V. Honavar, M. Jakiela, and R. Smith, Eds. Morgan Kaufmann, 1999, pp. 393–400.
- [91] P. Caleyary, G. Coray, A. Hertz, D. Kobler, and P. Kuonen, "A taxonomy of evolutionary algorithms in combinatorial optimization," *Journal of Heuristics*, vol. 5, pp. 145–158, 1999.
- [92] E. Talbi, "A taxonomy of hybrid metaheuristics," *Journal of Heuristics*, vol. 8, no. 5, pp. 541–564, 2002.
- [93] N. Krasnogor and S. Gustafson, "Toward truly "memetic" memetic algorithms: discussion and proof of concepts," in *Advances in Nature-Inspired Computation: The PPSN VII Workshops*, D. Corne, G. Fogel, W. Hart, J. Knowles, N. Krasnogor, R. Roy, J. E. Smith, and A. Tiwari, Eds. PEDAL (Parallel, Emergent and Distributed Architectures Lab). University of Reading. ISBN 0-9543481-0-9, 2002, pp. 9–10.
- [94] J. Smith, "The co-evolution of memetic algorithms for protein structure prediction," in *Recent Advances in Memetic Algorithms*, W. Hart, N. Krasnogor, and J. Smith, Eds. Springer, 2004, pp. 105–128.
- [95] —, "Co-evolving memetic algorithms: A learning approach to robust scalable optimisation," in *Proceedings of IEEE Congress on Evolutionary Computation: CEC-03*, 2003, pp. 498–505.
- [96] —, "Protein structure prediction with co-evolving memetic algorithms," in *Proceedings of IEEE Congress on Evolutionary Computation: CEC-03*, 2003, pp. 2346–2353.
- [97] N. Krasnogor, "Self-generating metaheuristics in bioinformatics: The protein structure comparison case," *Genetic Programming and Evolvable Machines. Kluwer academic Publishers*, vol. 5, no. 2, pp. 181–201, 2004.
- [98] N. Krasnogor and S. Gustafson, "A study on the use of "self-generation" in memetic algorithms," *Natural Computing*, vol. 3, no. 1, pp. 53–76, 2004.
- [99] P. Angeline, "Adaptive and self-adaptive evolutionary computations," in *Computational Intelligence*. IEEE Press, 1995, pp. 152–161.
- [100] J. Smith and T. Fogarty, "Operator and parameter adaptation in genetic algorithms," *Soft Computing*, vol. 1, no. 2, pp. 81–87, 1997.
- [101] P. Hansen and N. Mladenovic, "An introduction to variable neighborhood search," *Metaheuristics, Advances and Trends in Local Search Paradigms for Optimization*, pp. 433–458, 1999.
- [102] P. Merz and B. Freisleben, "Fitness landscapes, memetic algorithms, and greedy operators for graph bipartitioning," *Journal of Evolutionary Computation*, vol. 8, no. 1, pp. 61–91, 2000.
- [103] —, "On the effectiveness of evolutionary search in high-dimensional nk-landscapes," in *Proceedings of the 1998 IEEE International Conference on Evolutionary Computation*. IEEE Press, 1998, pp. 741–745.
- [104] T. Jones, "Evolutionary algorithms, fitness landscapes and search," Ph.D. dissertation, University of New Mexico, Albuquerque, NM, 1995.